

Page 1/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024 Version number 31 Revision: 13.07.2024

1 Identification of the hazardous chemical and of the supplier

· Product identifier

/ the mixture

· Trade name Konudur 170 TR-NA - Komponente A

Recommended use of the chemical and restrictions on

use · Application of the substance

e

Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Epoxy resin

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

No further relevant information available.

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department: msds@mc-bauchemie.de

2 Hazard identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· Label elements

• GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

· Hazard pictograms







GHS07 GHS08 GHS09

· Signal word Warning

Hazard-determining

components of labelling: epoxide derivates titanium dioxide

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

dioxirane

(Contd. on page 2)





Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024 Version number 31 Revision: 13.07.2024

Trade name Konudur 170 TR-NA - Komponente A

(Contd. of page 1)

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane

(1:2)

· Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause allergic skin reaction.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements P261 Avoid breathing dust/fume/ gas/mist/vapours/

spray.

P280 Wear protective gloves / eye protection / face

protection.

P281 Use personal protective equipment as required.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362 Take off contaminated clothing and wash before

reuse.

P363 Wash contaminated clothing before reuse.

· Other hazards

· Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

· Chemical characterisation: Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous compo	onents:	
CAS: 1675-54-3	epoxide derivates	50-70%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	≥10-<25%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane (1:2)	≥10-<25%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 13463-67-7	titanium dioxide	≥1-<1.5%
	Carc. 2, H351	
CAS: 4394-85-8	4-morpholinecarbaldehyde	≥0.1-<0.5%
	Skin Sens. 1, H317	
	(C	ontd. on page 3)

MY



Page 3/10

Safety Data Sheet according to P.U.(A) 310/2013

Revision: 13.07.2024 Printing date 13.07.2024 Version number 31

Trade name Konudur 170 TR-NA - Komponente A

(Contd. of page 2)

· Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

· After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

Information for doctor · Most important symptoms

and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· Special hazards arising from

the substance or mixture

No further relevant information available.

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and

emergency procedures Wear protective clothing.

· Environmental precautions: Inform respective authorities in case product reaches water or

sewage system.

· Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Ensure adequate ventilation.

· Reference to other sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Page 4/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024 Version number 31 Revision: 13.07.2024

Trade name Konudur 170 TR-NA - Komponente A

(Contd. of page 3)

See Section 13 for information on disposal.

7 Handling and storage

· Handling

· Precautions for safe handling Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· Conditions for safe storage, including any incompatibilities

·Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: None.
Storage class 10

8 Exposure controls and personal protection

· Additional information about

design of technical systems: No further data; see section 7.

· Control parameters

· Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

Personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

(Contd. on page 5)



Page 5/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024 Version number 31 Revision: 13.07.2024

Trade name Konudur 170 TR-NA - Komponente A

(Contd. of page 4)

· Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

• **Protection of hands:** Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

• Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

· Eye protection:

· Body protection:

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

Safety goggles.

Protective clothing

Suitable protective clothing should be worn when working with

epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.



Page 6/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024 Version number 31 Revision: 13.07.2024

Trade name Konudur 170 TR-NA - Komponente A

(Contd. of page 5)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Pasty
Colour: Whitish
Smell: Characteristic

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing pointNot determined
Initial boiling point and boiling range >200 °C

· Flash point: 151 °C

· Auto-ignition temperature 184 °C

· Auto-ignition temperature Product is not selfigniting.

• Explosive properties: Product is not explosive.

Steam pressure: Not determined.

Density at 20 °C 1.25 g/cm³

· Solubility in / Miscibility with

Water:

Not miscible or difficult to mix

· Viscosity:

dynamic: Not determined. kinematic: Not determined.

· Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability · Thermal decomposition /

conditions to be avoided:

No decomposition if used according to specifications.

· Possibility of hazardous reactions

No dangerous reactions known

· Conditions to avoid · Incompatible materials:

No further relevant information available. No further relevant information available.

· Hazardous decomposition

products: No dangerous decomposition products known

MY



Page 7/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024 Version number 31 Revision: 13.07.2024

Trade name Konudur 170 TR-NA - Komponente A

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values that are relevant for classification:

CAS: 1675-54-3 epoxide derivates

23000 mg/kg (rabbit) Dermal LD50

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

CAS: 13463-67-7 titanium dioxide

LD50 Oral >5000 mg/kg (rat) LD50 >10000 mg/kg (rabbit) Dermal Inhalative LC50/4 h >6.8 mg/l (rat)

· Primary irritant effect:

· Skin corrosion or irritation

Irritant for skin and mucous membranes.

· Serious eye damage or eye

irritation · Respiratory / skin

No irritant effect.

No sensitizing effect known.

sensitization

· Additional toxicological

information:

The product shows the following dangers according to the

calculation method of the General EC Classification Guidelines for

Preparations as issued in the latest version:

Irritant

· CMR effects (carcinogenity, mutagenicity and toxicity for

reproduction) Carc. 2

12 Ecological information

· Toxicity

· Aquatic toxicity:	· A	qι	ıatı	C	τοχ	KIC	ıτy	:
---------------------	-----	----	------	---	-----	-----	-----	---

CAS:	1675-54-3	epoxide	derivates
------	-----------	---------	-----------

IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (Oncorhynchus mykiss) EC50/48h 1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

(Contd. on page 8)



Page 8/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024 Version number 31 Revision: 13.07.2024

Trade name Konudur 170 TR-NA - Komponente A

(Contd. of page 7)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

LC50/96h >100 mg/l (Daphnia magna) EC50/96h >100 mg/l (Leucidus idus)

· Persistence and degradability No further relevant information available.

· Behaviour in environmental systems:

Bioaccumulative potential
 Mobility in soil
 No further relevant information available.
 No further relevant information available.

· Ecotoxical effects:

· Remark: Toxic for fish

· Additional ecological information:

General notes: Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

• Other adverse effects No further relevant information available.

13 Disposal information

· Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

Uncleaned packagings:

· Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14 Transportation information

· UN-Number · ADR, IMDG, IATA UN3082

· UN proper shipping name

· ADR, IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (epoxide derivates)

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (epoxide derivates), MARINE

POLLUTANT

(Contd. on page 9)



Page 9/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024 Version number 31 Revision: 13.07.2024

Trade name Konudur 170 TR-NA - Komponente A

	(Contd. of page
Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances an articles.
Label	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
Packing group	
ADR, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	Yes
- 1	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATÁ):	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances ar
	articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
Transport in bulk according to Anno	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	(-)
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (EPOXID
	DERIVATES), 9, III



Page 10/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024 Version number 31 Revision: 13.07.2024

Trade name Konudur 170 TR-NA - Komponente A

(Contd. of page 9)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· EHS reference list

CAS: 1675-54-3 epoxide derivates

Directive 2012/18/EU

Named dangerous

substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

 Qualifying quantity (tonnes) for the application of lower-

200 t tier requirements

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

Environment protection department. specification sheet:

· Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion or irritation - Category 2

Eye Irrit. 2: Serious eye damage or eye irritation - Category 2

Skin Sens. 1: Skin sensitization - Category 1

Carc. 2: Carcinogenicity - Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - chronic hazard -

Aquatic Chronic 3: Hazardous to the aquatic environment - chronic hazard -

Category 3

* * Data compared to the previous version altered.