

*

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024

Version number 35

Revision: 13.07.2024

Product identifier	
Trade name Recommended use of the chemical and restrictions or	MC-DUR 1101 - Komponente A
use	No further relevant information available.
· Application of the substance / the mixture	e Epoxy coating
Details of the supplier of the Manufacturer/Supplier:	e safety data sheet MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533
Informing department:	msds@mc-bauchemie.de
Hazard identification Classification of the substan Eye Dam. 1 H318 Causes se	nce or mixture erious eye damage.
Hazard identification Classification of the substat Eye Dam. 1 H318 Causes se Skin Sens. 1 H317 May cause	nce or mixture erious eye damage.
Hazard identification Classification of the substan Eye Dam. 1 H318 Causes se	nce or mixture erious eye damage.
Hazard identification Classification of the substat Eye Dam. 1 H318 Causes se Skin Sens. 1 H317 May cause Label elements	nce or mixture erious eye damage. e allergic skin reaction. The product is classified and labelled according to the Globa
Hazard identification Classification of the substat Eye Dam. 1 H318 Causes se Skin Sens. 1 H317 May cause Label elements GHS label elements	nce or mixture erious eye damage. e allergic skin reaction. The product is classified and labelled according to the Globa Harmonised System (GHS).
Hazard identification Classification of the substan Eye Dam. 1 H318 Causes se Skin Sens. 1 H317 May cause Label elements GHS label elements Hazard pictograms	nce or mixture erious eye damage. e allergic skin reaction. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05 GHS07
Hazard identification Classification of the substai Eye Dam. 1 H318 Causes se Skin Sens. 1 H317 May cause Label elements GHS label elements Hazard pictograms	nce or mixture erious eye damage. e allergic skin reaction. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05 GHS07 Danger Polymer Epoxidharz-Addukt
Hazard identification Classification of the substan Eye Dam. 1 H318 Causes se Skin Sens. 1 H317 May cause Label elements GHS label elements Hazard pictograms	nce or mixture erious eye damage. e allergic skin reaction. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05 GHS07 Danger Polymer Epoxidharz-Addukt Aminpolymer H318 Causes serious eye damage.
Hazard identification Classification of the substan Eye Dam. 1 H318 Causes se Skin Sens. 1 H317 May cause Label elements GHS label elements Hazard pictograms Signal word Hazard-determining components of labelling:	nce or mixture erious eye damage. e allergic skin reaction. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05 GHS07 Danger Polymer Epoxidharz-Addukt Aminpolymer

Page 1/9



Page 2/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024

Version number 35

Revision: 13.07.2024

Trade name MC-DUR 1101 - Komponente A

	P280	(Contd. of page 1) Wear protective gloves / eye protection / face
	P305+P351+P3	protection. 38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	P310	present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
	P321 P363	Specific treatment (see on this label). Wash contaminated clothing before reuse.
· Other hazards		-
· Results of PBT and vPvE	3 assessment	
· PBT: · vPvB:	Not applicable. Not applicable.	

3 Composition and information of the ingredients of the hazardous chemical

· Chemical characterisation: Mixtures

Resin mixture with colouring agents. Mixture consisting of the following components.

· Dangerous components:			
CAS: 260549-92-6	CAS: 260549-92-6 Polymer Epoxidharz-Addukt		
	Eye Dam. 1, H318		
CAS: 180583-06-6	Aminpolymer	<i>≥</i> 1-<10%	
	Skin Sens. 1, H317		
CAS: 112-57-2	3,6,9-triazaundecamethylenediamine	<i>≥</i> 0.25-<0.5%	
	Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317		
• Additional information For the wording of the listed hazard phrases refer to section 16.			

4 First-aid measures

· Description:

· Description of first aid measures General information Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air. · After inhalation Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice. In case of contact with skin, wash carefully with plenty of soap and · After skin contact water. Consult a doctor in case of skin reactions. · After eye contact Rinse opened eye for several minutes under running water. Call a doctor immediately · After swallowing Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor. (Contd. on page 3) MY



Page 3/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024

Version number 35

Revision: 13.07.2024

(Contd. of page 2)

Trade name MC-DUR 1101 - Komponente A

· Information for doctor

- Most important symptoms
- and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- Special hazards arising from
- the substance or mixture No further relevant information available.
- Advice for firefighters • Protective equipment:
- No special measures required.

6 Accidental release measures

Not required.
Prevent material from reaching sewage system, holes and cellars.
Dilute with much water.
: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

7 Handling and storage

· Handling

· Precautions for safe handling Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

(Contd. on page 4)

MY



Page 4/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024

Version number 35

Revision: 13.07.2024

Trade name MC-DUR 1101 - Komponente A

 Information about protection against explosions and fires: Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
 Conditions for safe storage, including any incompatibilities
 Storage
 Requirements to be met by storerooms and containers: No special requirements.
 Further information about storage conditions: Protect from heat and direct sunlight.
 Storage class

8 Exposure controls and personal protection

- Additional information about design of technical systems: No further data; see section 7.
- Control parameters
 Components with critical values that require
 monitoring at the workplace: The product does not contain any relevant quantitie
 - *monitoring at the workplace:* The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs	· DNELs				
CAS: 1	CAS: 112-57-2 3,6,9-triazaundecamethylenediamine				
Oral DNEL 0.53 mg/kg		0.53 mg/kg	ı bw/Tag (ArL)		
Derma	I DNEL	0.74 mg/kg	ı bw/day (ArL)		
Inhalat	ive DNEL	6940 mg/m	9 ³ (ArL)		
PNEC	s				
CAS: 1	112-57-2 3	,6,9-triazau	ndecamethylenediamine		
PNEC	9.73 mg/l	(BEL)			
	0.0068 m	g/l (Fresh w	ater)		
	0.0068 m	g/l (Mew)			
PNEC	0.343 mg	43 mg/kg dwt (Sediment)			
	3.43 mg/k	43 mg/kg dwt (Fresh water sediment)			
· Additi	Additional information:		The lists that were valid during the compilation were used as basis.		
	ure contro				
	Personal protective equipment				
	 General protective and hygienic measures 		Keep away from food, drink and animal feed.		
nygion	no medeu		Remove soiled, soaked clothing immediately.		
			Wash hands before breaks and at the end of work.		
			Avoid contact with eyes and skin.		
· Breathing equipment:		oment:	If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/		
			(Contd. on page 5)		



Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024

Version number 35

Revision: 13.07.2024

Page 5/9

Trade name MC-DUR 1101 - Komponente A

	(Orantid a frame
	Contd. of pag) white) in rooms that cannot be ventilated. If oxygen deficienc
	expected, use self-contained breathing apparatus. Obse
	wearing time limits according to §9 (3) GefStoffV in conjunct
	wearing time minis according to 39 (3) Gerston v in conjunct with BGR 190.
Protection of hands:	Selection of the glove material on consideration of the penetral
	times, rates of diffusion and the degradation
Material of gloves	You can find help with choosing gloves on the website http
5	www.bgbau.de/fileadmin/Gisbau/Projekte.pdf
	For example, we recommend the Sol-vex 37-900 protective glo
	from Ansell GmbH. The breakthrough time of the protective glo
	can be found under point 8 "Penetration time of the glove materi
	The selection of a suitable glove depends not only on the mater
	but also on other quality features and varies from manufacture
	manufacturer. As the product
	is a preparation of several substances, the resistance of glo
	materials cannot be calculated in advance and must therefore
	checked before use.
	Nitrile rubber
	Recommended material thickness:≥ 0.4 mm
Penetration time of glove	
material	The breakthrough times of the Sol-vex 37-900 protective glo
	are around 8 hours.
	The following applies to all other gloves:
	The exact breakthrough time must be obtained from the protect
	glove manufacturer and adhered to.
	Nitrile rubber
	Material thickness: \geq 0.40 mm
	Penetration time: \geq 480 min
	Butyl rubber:
	Material thickness: ≥ 0.5 mm
	Penetration time: \geq 480 min
Eye protection:	Tight-fitting safety goggles.
	Safety goggles.
Body protection:	Protective clothing
	Suitable protective clothing should be worn when working v
	epoxy resins. In addition to normal work clothing (long trouse
	long-sleeved shirt or T-shirt), disposable overalls, apro
	overshoes, sleeve protectors etc. may be necessary depending
	the activity. Uncovered areas of skin should be avoided as far
	possible, even in hot weather. If the work involves kneeling,
	lower leg area should be protected by protective trousers.

(Contd. on page 6)



Page 6/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024

Version number 35

Revision: 13.07.2024

Trade name MC-DUR 1101 - Komponente A

(Contd. of page 5)

 Information on basic physical and General Information 	a chemical properties	
· Appearance:		
Form:	Fluid	
Colour:	Transparent	
· Smell:	Characteristic	
· pH-value:	Not determined.	
· Change in condition		
Melting point/freezing point	<0 °C	
Initial boiling point and boiling i	range 100 °C	
· Flash point:	151 °C	
· Auto-ignition temperature	Product is not selfigniting.	
• Explosive properties:	Product is not explosive.	
· Steam pressure at 20 °C:	23 hPa	
Vapour pressure at 50 °C:	<5 hPa	
· Density at 20 °C	1.07 g/cm³	
· Solubility in / Miscibility with		
Water:	Fully miscible	
· Viscosity:		
dynamic:	Not determined.	
kinematic:	Not determined.	
· Other information		

Reactivity	No further relevant information available.	
Chemical stability		
Thermal decomposition /		
conditions to be avoided:	No decomposition if used according to specifications.	
Possibility of hazardous		
reactions	No dangerous reactions known	
Conditions to avoid	No further relevant information available.	
Incompatible materials:	No further relevant information available.	
Hazardous decomposition		
products:	No dangerous decomposition products known	

(Contd. on page 7)



Page 7/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024

Version number 35

Revision: 13.07.2024

Trade name MC-DUR 1101 - Komponente A

(Contd. of page 6)

Information on toxicological	Information on toxicological effects		
Acute toxicity			
LD/LC50 values that are relevant for classification:			
CAS: 112-57-2 3,6,9-triazaundecamethylenediamine			
Oral LD50 2140 mg/kg (rat) Dermal LD50 1260 mg/kg (rabbit) • Primary irritant effect: • Oral			
		Serious eye damage or eye irritation	Strong irritant with the danger of severe eye injury.
		Respiratory / skin	
sensitization	Sensitization possible by skin contact.		
Additional toxicological			
information:	The product shows the following dangers according to		
	calculation method of the General EC Classification Guideline Preparations as issued in the latest version:		
	Irritant		
Foological information			
Ecological information			
Toxicity			
Toxicity Aquatic toxicity:			
Toxicity			
Toxicity Aquatic toxicity: CAS: 112-57-2 3,6,9-triazaun EC50/72h 2.1 mg/l (algae)			
Toxicity Aquatic toxicity: CAS: 112-57-2 3,6,9-triazaun EC50/72h 2.1 mg/l (algae) LC50/96h 420 mg/l (Gup)	decamethylenediamine		
ToxicityAquatic toxicity:CAS: 112-57-2 3,6,9-triazaunEC50/72h2.1 mg/l (algae)LC50/96h420 mg/l (Gup)EC50/48h24.1 mg/l (DaphniaPersistence and degradabili	decamethylenediamine magna) ty No further relevant information available.		
ToxicityAquatic toxicity:CAS: 112-57-2 3,6,9-triazaunEC50/72h2.1 mg/l (algae)LC50/96h420 mg/l (Gup)EC50/48h24.1 mg/l (DaphniaPersistence and degradabiliBehaviour in environmental	decamethylenediamine magna) ty No further relevant information available. systems:		
ToxicityAquatic toxicity:CAS: 112-57-2 3,6,9-triazaunEC50/72h2.1 mg/l (algae)LC50/96h420 mg/l (Gup)EC50/48h24.1 mg/l (DaphniaPersistence and degradabiliBehaviour in environmentalBioaccumulative potential	decamethylenediamine magna) ty No further relevant information available. systems: No further relevant information available.		
ToxicityAquatic toxicity:CAS: 112-57-2 3,6,9-triazaunEC50/72h2.1 mg/l (algae)LC50/96h420 mg/l (Gup)EC50/48h24.1 mg/l (DaphniaPersistence and degradabiliBehaviour in environmentalBioaccumulative potentialMobility in soil	decamethylenediamine magna) ty No further relevant information available. systems: No further relevant information available. No further relevant information available.		
ToxicityAquatic toxicity:CAS: 112-57-2 3,6,9-triazaunEC50/72h2.1 mg/l (algae)LC50/96h420 mg/l (Gup)EC50/48h24.1 mg/l (DaphniaPersistence and degradabiliBehaviour in environmentalBioaccumulative potentialMobility in soilAdditional ecological inform	ndecamethylenediamine magna) ty No further relevant information available. systems: No further relevant information available. No further relevant information available. no further relevant information available. nation:		
ToxicityAquatic toxicity:CAS: 112-57-2 3,6,9-triazaunEC50/72h2.1 mg/l (algae)LC50/96h420 mg/l (Gup)EC50/48h24.1 mg/l (DaphniaPersistence and degradabiliBehaviour in environmentalBioaccumulative potentialMobility in soilAdditional ecological inform	decamethylenediamine magna) ty No further relevant information available. systems: No further relevant information available. No further relevant information available. No further relevant information available. Do not allow product to reach ground water, water bodie sewage system.		
ToxicityAquatic toxicity:CAS: 112-57-2 3,6,9-triazaumEC50/72h2.1 mg/l (algae)LC50/96h420 mg/l (Gup)EC50/48h24.1 mg/l (DaphniaPersistence and degradabiliBehaviour in environmentalBioaccumulative potentialMobility in soilAdditional ecological informGeneral notes:	decamethylenediamine ty No further relevant information available. systems: No further relevant information available. No further relevant information available. No further relevant information available. nation: Do not allow product to reach ground water, water bodie sewage system. Danger to drinking water if even small quantities leak into soil.		
EC50/72h2.1 mg/l (algae)LC50/96h420 mg/l (Gup)EC50/48h24.1 mg/l (DaphniaPersistence and degradabiliBehaviour in environmentalBioaccumulative potentialMobility in soilAdditional ecological informGeneral notes:Results of PBT and vPvB as	decamethylenediamine ty No further relevant information available. systems: No further relevant information available. No further relevant information available. No further relevant information available. nation: Do not allow product to reach ground water, water bodie sewage system. Danger to drinking water if even small quantities leak into soil. sessment		
ToxicityAquatic toxicity:CAS: 112-57-2 3,6,9-triazaumEC50/72h2.1 mg/l (algae)LC50/96h420 mg/l (Gup)EC50/48h24.1 mg/l (DaphniaPersistence and degradabiliBehaviour in environmentalBioaccumulative potentialMobility in soilAdditional ecological informGeneral notes:	decamethylenediamine ty No further relevant information available. systems: No further relevant information available. No further relevant information available. No further relevant information available. nation: Do not allow product to reach ground water, water bodie sewage system. Danger to drinking water if even small quantities leak into soil.		

(Contd. on page 8)



Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024

Version number 35

Revision: 13.07.2024

Trade name MC-DUR 1101 - Komponente A

(Contd. of page 7)

Page 8/9

13 Disposal information • Waste treatment methods • Recommendation • Uncleaned packagings: • Recommendation: • Uncleaned packagings: • Recommendation: • Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

 Recommended cleaning agent:

Water, if necessary with cleaning agent.

14 Transportation information

· UN-Number · ADR, ADN, IMDG, IATA	Void
· UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· Packing group · ADR, IMDG, IATA	Void
 Environmental hazards: Marine pollutant: 	No
· Special precautions for user	Not applicable.
 Transport in bulk according to Annex Marpol and the IBC Code 	(II of Not applicable.
· UN "Model Regulation":	Void

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

· EHS reference list

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

Directive 2012/18/EU

 Named dangerous substances - ANNEX I

None of the ingredients is listed.

(Contd. on page 9)

MY



Page 9/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.07.2024

Version number 35

Revision: 13.07.2024

Trade name MC-DUR 1101 - Komponente A

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 Department issuing data specification sheet: Contact: 	Environment protection department.
Abbreviations and acronyms: Abbreviations and acronyms: * Data compared to the previous version altered.	 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral – Category 4 Skin Corr. 1: Skin corrosion or irritation – Category 1 Eye Dam. 1: Serious eye damage or eye irritation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - chronic hazard – Category 2
	MX-